



HI-THANE™

Innovative polyurethane
laminating adhesives for
flexible packaging

SONGWON is a leading specialist in
laminating adhesive technology for
the plastic film packaging industry.

Our extended portfolio of HI-THANE™ polyurethanes
enables us to design customized formulations for our
customers.


Thanks to their excellent physical and technical properties,
HI-THANE™ high performance laminating adhesives are
widely used by film converters to improve operational
efficiency and profitability.

It's all about **the chemistry™**



SONGWON – Extensive experience in flexible packaging

Wide range of solvent-based laminating systems



Suitable for all flexible packaging applications
Cutting-edge quality
FDA compliant

Comprehensive technical expertise



Dedicated laminating adhesives testing laboratory in South Korea
Customized formulations

Proven reliability



More than 35 years manufacturing experience in South Korea
Backward integration into polyester polyol production
Global sales organization channels in Asia, Europe and North America

Strong commitment



Continuous innovation to meet new industry standards

HI-THANE™ laminating adhesives generate significant value for film converters through increased productivity and profitability...

Higher productivity



Fast curing enables high bond strength to be obtained within a few hours, allowing slitting within 12-24 hours and quicker laminate turnover
Long pot life facilitates processing

Increased profitability



High solid content systems reduce solvent disposal costs
Very good wetting properties help to reduce coating weights and film lamination costs
Exceptional film transparency enhances appearance, adding value throughout the chain
Very high resistance to boiling water and retorting prevents de-lamination of film layers and reduces potential waste disposal costs

Technology & compliance



Solvent-based aromatic polyurethanes
Suitable for all flexible packaging applications
FDA compliant

HI-THANE™ laminating adhesives recommended for flexible packaging

	HI-THANE™ A-3165S	HI-THANE™ A-3165SL	HI-THANE™ A-3070	HI-THANE™ A-4650R	HI-THANE™ A-770M	HI-THANE™ A-7500L	HI-THANE™ A-7980
A-side chemistry	Polyester based PU	Polyester based PU	Polyester based PU	Polyester based PU	Polyether based PU	Isocyanate NCO	Isocyanate NCO
Applications	Plastic films Aluminum foil	Plastic films Aluminum foil	Plastic films Aluminum foil	Plastic films Aluminum foil	Plastic films Aluminum foil	Plastic films Aluminum foil	Plastic films Aluminum foil
Type	Solvent-based	Solvent-based	Solvent-based	Solvent-based	Solvent-based	Non solvent-based	Non solvent-based
Appearance	Yellowish	Yellowish	Yellowish	Yellowish	Yellowish	Yellowish	Yellowish
Total solid content (% , w/w)	65	65	70	65	70	100	100
Viscosity (Brook-field cps at 25°C)	2000 ~ 4000	1200 ~ 2000	8000 ~ 12000	2000 ~ 5000	5000 ~ 15000	400 ~ 800 (at 40°C)	1000 ~ 3000 (at 40°C)
Solvent	Ethyl acetate	Ethyl acetate	Ethyl acetate	Ethyl acetate	Ethyl acetate	Not applicable	Not applicable
Recommended hardeners	HI-THANE™ CA-75	HI-THANE™ CA-75	HI-THANE™ CA-75	HI-THANE™ CA-75	HI-THANE™ CA-280H	HI-THANE™ A-6500A	HI-THANE™ A-6962C
B-side chemistry	Isocyanate NCO	Isocyanate NCO	Isocyanate NCO	Isocyanate NCO	Isocyanate NCO	- OH	- OH

HI-THANE™ adhesives key properties

	HI-THANE™ A-3165S	HI-THANE™ A-3165SL	HI-THANE™ A-3070	HI-THANE™ A-4650R	HI-THANE™ A-770M	HI-THANE™ A-7500L	HI-THANE™ A-7980
Grade	General, medium and high performance	General, medium and high performance	General, medium and high performance	Medium and high performance	General performance	General performance	General performance
Film transparency	Good	Good	Good	Good	Very good	Good	Very good
Bonding strength	Very good	Good	Good	Very good	Good	Average	Good
Fast cure properties	Good	Good	Good	Good	Very good	Good	Very good
Reduced metalized layer transfer	Not applicable	Not applicable	Not applicable	Not applicable	Not applicable	Very good	Very good
Resistance to boiling water and retorting	Good	Good	Good	Very good	Average	Good	Good
Wetting properties	Very good	Very good	Very good	Very good	Very good	Very good	Very good

Storage conditions



HI-THANE™ laminating adhesives should be stored indoors, in closed containers, in a dry place at temperatures between 5 and 40°C.

Exposure to direct sunlight should be avoided.

Shelf life



HI-THANE™ laminating adhesives are stable for 12 months, provided they are stored under the above conditions.





For further information, please go to:

www.songwon.com

tpuspu@songwon.com

SONGWON provides customers with warranties and representations as to the chemical or technical specifications, compositions and/or the suitability for use for any particular purpose exclusively in individual written agreements.

The facts and figures contained herein have been carefully compiled to the best of SONGWON's knowledge but are essentially intended for informational purposes only.

SONGWON Industrial Group does not accept any liability whatsoever for any information, reference or advice provided in this document or any similar SONGWON publication.

Version 4.2, August 2022